



Eterna ATF Dexron II

Automatic Transmission Fluid

Eterna ATF Dexron II is a mineral oil based automatic transmission fluid designed with superior oxidation stability and friction retention to meet the obsolete Dexron II specification requirements of many automatic transmissions, power shift transmissions and power steering units.

Applications

- Approved and recommended for all automatic transmissions
- Power steering units
- Hydraulic power systems

Performance Features and Benefits

- **Friction modified**
Provides consistent, reliable, smooth and trouble-free operation of automotive transmission systems
- **High oxidation resistance**
Resistant to oil degradation due to oxidative conditions often encountered at high temperatures.
- **Excellent shear-stability**
A special viscosity index improver ensures ATF maintains its viscosity for a longer period
- **Dependable anti-wear protection**
Long component life

Typical Physical Characteristics

Name	ATF Dexron II
Kinematic Viscosity @ 40°C (mm ² /s)	39.03
@ 100°C (mm ² /s)	7.25
Viscosity Index	152
Density @20°C kg/l	0.88
Flash Point °C (COC)	192
Pour Point °C	< - 42
Friction Modified	Yes
Base	Mineral
Colour	Red

These characteristics are typical of current production. Whilst future production will conform to Eterna specifications, variations in these characteristics may occur.

Health, Safety & Environment

Eterna ATF is unlikely to present any significant HSE hazard when properly used in the recommended application whilst good industrial, personal hygiene and environmental standards are maintained.

Avoid contact with skin. Use impervious gloves with used oil. In the event of skin contact, wash immediately with soap and water.

Dispose used oil safely. Do not discharge into drains, soil or water.

Advice

Advice on applications not covered in this leaflet may be obtained from the Lubricants Department, Eterna PLC, 5a Oba Adeyinka Oyekan Avenue, Ikoyi.

Tel: 01-8981836, 8981842, 2691651

