



Eterna EPX Oils

Extreme-pressure automotive gear lubricants

Eterna EPX Oils are specially blended automotive gear lubricants recommended for use in manual gearboxes of all passenger cars and commercial vehicles where high extreme pressure additive levels are desired.

Applications

- **Manual gearboxes**
EPX Oils are specially formulated primarily for the lubrication of manual gearboxes of passenger cars and commercial vehicles and construction equipment's where higher additive API quality level of GL-5 would not interfere with gear selection.

Performance Features

- **Comprehensive additive package**
Specially selected additives impart good anti-wear, oxidation stability and anti-rust characteristics.

Performance Specifications

API Service Classification - GL-5

Typical Physical Characteristics

Name	80W-90	85W-90	85W-140
SAE Viscosity Grade	80W-90	85W-90	85W-140
Kinematic Viscosity @ 40°C (mm ² /s)	194	194	415
@ 100°C (mm ² /s)	14	16.5	28.5
Viscosity Index	97	97	96
Density @15°C kg/l	0.896	0.895	0.9
Flash Point °C (COC)	220	220	230
Pour Point °C	-15	-15	-12
API Classification	GL-5	GL-5	GL-5

These characteristics are typical of current production. Whilst future production will conform to Eterna specifications, variations in these characteristics may occur.

Health, Safety & Environment

Eterna EPX Oils are unlikely to present any significant HSE hazard when properly used in the recommended application whilst good industrial, personal hygiene and environmental standards are maintained.

Avoid contact with skin. Use impervious gloves with used oil. In the event of skin contact, wash immediately with soap and water.

Dispose used oil safely. Do not discharge into drains, soil, or water.

Advice

Advice on applications not covered in this leaflet may be obtained from the Lubricants Department, Eterna PLC, 5a Oba Adeyinka Oyekan Avenue, Ikoyi.

Tel: 01-8981836, 8981842, 2691651