



GAS ENGINE OIL 30

Eterna Gas Engine Oil SAE 30 is a Low Ash Gas Engine Oil, formulated from select base stocks blended with advanced technology additive package to provide outstanding protection against piston, rings, liner scuffing and wear in engines that use gaseous fuels. This oil has ability to optimize the life of all engine components while achieving extended oil change intervals.

Applications

- **Gas Engines**
Recommended in 4-Stroke and Selected 2-Stroke engines powered by natural or synthetic gas.

Performance Features

- **Outstanding performance**
Excellent anti-oxidation/ nitration properties with reduced carbon and sludge formation.
- **Advanced additive technology**
Advanced additive technology produces a shear-stable gas engine oil that withstand the highest mechanical loads whilst providing outstanding wear protection under all operating conditions.
- **Compatibility**
Compatible with exhaust catalyst applications that require low phosphorous oil
- **Extended oil drain capability**
Provides outstanding performance for applications requiring extended oil drain intervals.

Advantages

- Longer engine and oil life and lower maintenance costs.
- Cleaner engines and extended filter life
- Protects engine components against corrosive wear
- Provide excellent thermal stability

Typical Physical Characteristics

SAE Viscosity Grade	SAE 30
Viscosity @ 40°C, cSt 100°C, cSt	99.0 11.3
Viscosity Index (Min.)	96
Density @ 15°C, kg/l	0.880
Flash Point °C (IP 36) (Cleveland Open Cup)	220
Pour Point, °C	-18
TBN mg KOH/g	4.5
Sulphated Ash Content % wt.	0.5

These characteristics are typical of current production. Whilst future production will conform to Eterna Specifications, variations in these characteristics may occur.

Health, Safety & Environment

Eterna Gas Engine Oil is unlikely to present any significant HSE hazard when properly used in the recommended application whilst good industrial, personal hygiene and environmental standards are maintained.

Avoid contact with skin. Use impervious gloves with used oil. In the event of skin contact, wash immediately with soap and water.

Dispose used oil safely. Do not discharge into drains, soil or water.

Advice

Advice on applications not covered in this leaflet may be obtained from the Lubricants Department, Eterna Plc, 5a Oba Adeyinka Oyekan Avenue (formerly Second Avenue), Ikoyi, Lagos.

Tel: 01-460 5317, 460 5318, 4604062