



Eterna HD Super 10W

Longer engine life for diesel engines

HD Super 10W Oil is a high performance heavy duty engine lubricant with special performance specification for good piston deposit control.

Applications

- Eterna HD Super 10W is suitable for hydraulic system *recommending SAE 10W*
- It is suitable for turbo-charged or naturally aspirated heavy duty
- Can be described as a hydraulic Oil for Caterpillar Engines

Performance Features

- Reduced Engine wear under sever operating conditions
- Reduced bearing related wear.
- Good piston deposit control.
- Protection against rust and corrosion

Performance Specifications:

API Classifications - CF/SF

HSE: Health, Safety & Environment

HD Super 10W is unlikely to present any significant HSE hazard when properly used in the recommended application whilst good industrial, personal hygiene and environmental standards are maintained.

Avoid contact with skin. Use impervious gloves with used oil. In the event of skin contact, wash immediately with soap and water.

Dispose used oil safely. Do not discharge into drains, soil or water.

Advice

Advice on applications not covered in this leaflet may be obtained from Eterna PLC, 5a Oba Adeyinka Oyekan Avenue, Ikoyi

Tel: 01-8981836, 8981842, 2691651

Typical Physical Characteristics	10W
HD Super 10W API CF/SF	
SAE Viscosity Grade	10
Kinematic Viscosity @ 40 100°C	35.5 5.8
Viscosity Index min	104
Density @ 15°C	0.877
Flash Point °C (Cleveland Open Cup)	212
Pour Point °C	-12
TBN	6.0
Base	mineral

These characteristics are typical of current production. Whilst future production will conform to Eterna specification, variations in these characteristics may occur.