



# Multimax SJ 20W-50

## Premium multigrade motor oil

Multimax 20W-50 SJ is a guaranteed quality lubricant based on a blend of high viscosity index mineral oils and selected additives. It is blended to provide dependable engine protection in passenger and light / medium commercial vehicles in most motoring conditions.

### Applications

#### **Passenger car & SUV engines:**

Naturally aspirated passenger car & SUV engines fueled by gasoline, diesel or LPG

### Performance Features and Benefits

- **Catalyst proven**  
Exceeds industry standards
- **Dependable protection**  
All-year-round engine protection
- **High oxidation resistance**  
Long oil life.
- **Excellent engine cleanliness and low combustion residues**  
Superior detergent and dispersant properties ensure optimum performance and maximum life for the engine.
- **Superior viscosity retention**  
High Viscosity Index ensures adequate oil film strength at all operating temperatures.
- **Superior foaming characteristics**  
Do not foam, ensures superior lubrication with agitation.
- **Excellent Cold starting characteristics.**  
Minimizes engine wear, ensure long useful engine life

### Performance Specifications

Multimax 20W-50 SJ exceeds the following industry standards:

API Service Classification - SJ/CF

### HSE: Health, Safety & Environment

Multimax 20W-50 SJ is unlikely to present any significant

HSE hazard when properly used in the recommended application whilst good industrial, personal hygiene and environmental standards are maintained.

Avoid contact with skin. Use impervious gloves with used oil. In the event of skin contact, wash immediately with soap and water.

Dispose used oil safely. Do not discharge into drains, soil or water.

### Advice

Advice on applications not covered in this leaflet may be obtained from Eterna PLC, 5a Oba Adeyinka Oyekan Avenue, Ikoyi

Tel: 01-8981836, 8981842, 2691651

### Typical Physical Characteristics

Name	Multimax SJ
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	18
Viscosity Index	120 min
Density @20°C kg/l	0.89
Flash Point °C (COC)	240
Pour Point °C	-24
TBN	9
Base	Mineral

*These characteristics are typical of current production. Whilst future production will conform to Eterna specification, variations in these characteristics may occur.*