



Eterna Multimax SJ

Premium multigrade motor oil

Multimax SJ is a guaranteed quality lubricant based on a blend of high viscosity index mineral oils and selected additives. It is blended to provide dependable engine protection in passenger and light / medium commercial vehicles in most motoring conditions.

Applications

Passenger car & SUV engines:

Naturally aspirated passenger car & SUV engines fuelled by gasoline, diesel or LPG

Performance Features

- **Catalyst proven**
Exceeds industry standards
- **Dependable protection**
All-year-round engine protection
- **High oxidation resistance**
Long oil life.
- **Excellent engine cleanliness and low combustion residues**
Superior detergent and dispersant properties ensure optimum performance and maximum life for the engine.
- **Superior viscosity retention**
High Viscosity Index ensures adequate oil film strength at all operating temperatures.
- **Superior foaming characteristics**
Do not foam, ensures superior lubrication with agitation.
- **Excellent Cold starting characteristics.**
Minimizes engine wear, ensure long useful engine life

Performance Specifications

Multimax SJ exceeds the following industry standards:

API Service Classification SJ/CF

HSE: Health, Safety & Environment

Multimax is unlikely to present any significant HSE hazard when properly used in the

recommended application whilst good industrial, personal hygiene and environmental standards are maintained.

Avoid contact with skin. Use impervious gloves with used oil. In the event of skin contact, wash immediately with soap and water.

Dispose used oil safely. Do not discharge into drains, soil or water.

Advice

Advice on applications not covered in this leaflet may be obtained from Eterna PLC, 5a Oba Adeyinka Oyekan Avenue, Ikoyi

Tel: 01-8981836, 8981842, 2691651

Typical Physical Characteristics

Multimax	20W-50
Kinematic Viscosity@ 40°C cSt 100°C cSt	report 18.00
Viscosity Index	120 min
Density @ 20°C	0.89
Flash Point °C COC	240
Pour Point °C	-24
TBN	9.0
Base	mineral

These characteristics are typical of current production. Whilst future production will conform to Eterna specification, variations in these characteristics may occur.