



# Multimax SL Super 20W-50

## *Ultimate protection for performance motoring*

Multimax SL Super is a unique, ultimate quality lubricant based on a blend of high viscosity index mineral oils and carefully selected additives. It is specially formulated to give ultimate all-year-round engine protection and performance plus superior fuel economy in modern passenger cars fueled with gasoline, diesel, or LPG.

### Applications

- All naturally aspirated, fuel injected, turbocharged and multi valve passenger car engines fueled by gasoline, diesel, or LPG.

### Performance Features and Benefits

- **Catalyst and turbo compatible**  
Exceed industry standards
- **Dependable protection**  
All-year-round engine protection
- **High oxidation resistance**  
Long oil life.
- **Excellent engine cleanliness and low combustion residues**  
Superior detergent and dispersant properties ensure optimum performance and maximum life for the engine.
- **Superior viscosity retention**  
High Viscosity Index ensures adequate oil film strength at all operating temperatures.
- **Excellent Cold starting characteristics.**  
Minimizes engine wear, ensure long useful engine life

### Performance Specifications

Eterna Multimax SL meets the requirements of all major car manufacturers and the following industry standards: API: SL/CF

### HSE: Health, Safety & Environment

Multimax SJ is unlikely to present any significant HSE hazard when properly used in the recommended application whilst good industrial, personal hygiene and environmental standards are maintained.

Avoid contact with skin. Use impervious gloves with used oil. In the event of skin contact, wash immediately with soap and water.

Dispose used oil safely. Do not discharge into drains, soil, or water.

### Advice

Advice on applications not covered in this leaflet may be obtained from Eterna PLC, 5a Oba Adeyinka Oyekan Avenue, Ikoyi

Tel: 01-8981836, 8981842, 2691651

### Typical Physical Characteristics

Name	Multimax SL Super
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	18
Viscosity Index	120 min
Density @20°C kg/l	0.891
Flash Point °C (COC)	230 min
Pour Point °C	-18
TBN	7.5
Base	Mineral

*These characteristics are typical of current production. Whilst future production will conform to Eterna specification, variations in these characteristics may occur.*