

TPP 40

High-Performance Diesel Engine Oil

Eterna TPP 40 is a range of high-performance diesel engine oil specially formulated to provide ultimate all-round performance in modern marine and power generation four stroke engines operating on distillate fuels.

Applications

 Eterna TPP 40 is designed for use in modern marine propulsion and power generation engines requiring an API CF performance level.

Performance Features and Benefits

- Excellent anti-wear performance
 Proven anti-wear additives are incorporated to be effective throughout the range of operating conditions and for longer engine life.
- · High alkalinity reserve

Excellent total base number (TBN) retention and more alkalinity to control acid formations giving long term resistance to corrosive engine wear.

 Excellent thermal and oxidation stability

Execllent resistance to oxidation ensuring longer oil life.

• Excellent load carrying capabilities

Performance Specifications

TPP 40 meets the following performance standard:

API: CF

HSE: Health, Safety & Environment

TPP 40 Oil is unlikely to present any significant HSE hazard when properly used in the recommended application whilst good industrial, personal hygiene and environmental standards are maintained.

Avoid contact with skin. Use impervious gloves with used oil. In the event of skin contact, wash immediately with soap and water.

Dispose used oil safely. Do not discharge into drains, soil, or water.

Typical Physical Characteristics

Name	Units	TPP 40
SAE Viscosity Grade		40
Kinematic Viscosity		
@ 40°C	mm²/s	130
@ 100°C	mm²/s	14.5
Viscosity Index		96
Density @15°C	kg/l	0.890
Flash Point (COC)	°C	220
Pour Point	°C	-12
TBN	mg KOH/g	15

These characteristics are typical of current production. Whilst future production will conform to Eterna specification, variations in these characteristics may occur.

Advice

Advice on applications not covered in this leaflet may be obtained from Eterna PLC, 5a Oba Adeyinka Oyekan Avenue, Ikoyi.

Tel: 01-8981836, 8981842, 2691651